

## MISTER BLISTER

### METHYLENE CHLORIDE FREE PAINT REMOVER LIQUID



#### DESCRIPTION

**MISTER BLISTER** is a gel-based paint remover that quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal. For use by: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. For use on: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

#### APPLICATIONS

For removal of paint, decals, lacquer, gaskets, glue, carbon deposits, silicone, simulated wood paneling and other materials from metal, wood, brick, ceramic, and natural stone surfaces. Areas of use include auto dealerships, paint shops, factories, motels, hotels, schools, hospitals, homes and restaurants.

#### FEATURES & BENEFITS

- Versatile, multipurpose product removes a broad range of materials from most surfaces
- Thick formula clings to vertical surfaces, increasing contact time
- Works quickly and efficiently

#### SPECIFICATIONS

**FORM:** Solvent-Based Liquid  
**ODOR:** Acetone  
**COLOR:** Clear Blue-Green  
**DETERGENCY:** Strong  
**TOXICITY:** 1000 ppm  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year +  
**% VOC'S:** 5%

**FLASH POINT:** N/A  
**BOILING POINT:** N/A  
**SOLUBILITY IN WATER:** 100%  
**SPECIFIC GRAVITY:** 0.95-0.98  
**% VOLATILE BY VOLUME:** 85.1%  
**pH:** N/A  
**VISCOSITY:** 1000-1500 cps  
**BIODEGRADABILITY:** No

#### LABEL INFORMATION

##### MISTER BLISTER METHYLENE CHLORIDE FREE PAINT REMOVER

Gel-based paint remover quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. The methylene chloride free formula is a safer alternative to paint removal. For use by: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. For use on: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

**DIRECTIONS FOR USE:** Preclean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint is thoroughly wrinkled or bubbled. Flush with water or solvent. Use a scraper or wire brush in cracks, crevices or on stubborn accumulation. On painted floors, a squeegee may be used to move the stripper from one area to another when finished, and compound may be reused. Add new product periodically.

**DANGER:** Highly flammable liquid and vapor. Causes severe skin burns and serious eye damage. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection/protective clothing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use alcohol resistant foam, Carbon dioxide, or dry powder. Store locked up in a well ventilated place. Keep cool. Dispose of contents/container in accordance with local, state, and federal law. Do not breathe dusts or mists. Wash hands with soap and water thoroughly after handling. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Use only outdoors or in a well ventilated area. Call a poison center/doctor if you feel unwell. Do not eat, drink, or smoke when using this product. Get medical advice/attention if you feel unwell.

 **WARNING:** This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONTAINS (CAS#):** Dioxolane (646-06-0), Acetone (67-64-1), Dimethyl Carbonate (616-38-6), Monethanolamine (141-43-5), Isopropylidene Glycol (100-79-8).

#### PACKAGING INFORMATION

Available in 4 x 1 gallons, 5 gallon pails and 55 gallon drums.

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B

NFPA	
3 1	0 0

FIRE HAZARD  
REACTIVITY  
SPECIAL