

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: 484124
Product Name: Screen Clean
Revision Date: Feb 07, 2024 **Date Printed:** Feb 07, 2024
Version: 3.0 **Supersedes Date:** Jul 01, 2020
Manufacturer's Name: Zenex International
Address: 1 Zenex Circle Cleveland, OH, US, 44146
Emergency Phone: 1-800-535-5053
Information Phone Number: (440)-232-4155
Fax:
Product/Recommended Uses: Electronic Screen Cleaner

SECTION 2) HAZARDS IDENTIFICATION

Classification

Flammable Liquids - Category 2
Eye Irritation - Category 2A
Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor.

Hazardous Statements - Health

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves, eye protection and face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing mist or vapors.

P271 - Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

P370 + P378 - In case of fire: Use alcohol resistant foam, carbon dioxide or water fog to extinguish.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000067-63-0	ISOPROPYL ALCOHOL	65% - 85%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.
If exposed/feel unwell/concerned: Get medical attention.

Eye Contact

If irritation occurs, rinse eyes cautiously with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

Skin Contact

Rinse/wash with lukewarm, gently flowing water and mild soap for at least 15 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

Ingestion

Rinse mouth. Give two glasses of water. If you feel unwell or if concerned: Get medical attention. Do NOT induce vomiting unless under the advice of doctor or POISON CENTER. Note: Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog, alcohol resistant foam and carbon dioxide.

Dry chemical, sand or earth may be used for small fires only.

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

Fire-Fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Do not touch or walk through spilled material. Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Pick up with mop or wet vac. Rinse spill area with water.

Recommended Equipment

See section 8 for specifics on protective personal equipment (PPE).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Store at temperatures under 120°F.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY. FOR USE BY TRAINED PERSONNEL ONLY. KEEP FROM FREEZING.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (mg/m ³)	OSHA TWA (ppm)	OSHA STEL (mg/m ³)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	ACGIH TWA (mg/m ³)
ISOPROPYL ALCOHOL	980	400					1	

Chemical Name	ACGIH TWA (ppm)	ACGIH STEL (mg/m ³)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	NIOSH TWA (mg/m ³)	NIOSH TWA (ppm)
ISOPROPYL ALCOHOL	200		400	A4	Eye & URT irr; CNS impair	A4; BEI	980	400

Chemical Name	NIOSH STEL (mg/m ³)	NIOSH STEL (ppm)	NIOSH Carcinogen
ISOPROPYL ALCOHOL	1225	500	

(C) - Ceiling limit, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.01 lb/gal
Density VOC	4.91 lb/gal
% VOC	70%
Appearance	Wipes moistened with a clear liquid
Odor Threshold	N.A.
Odor Description	Alcohol
pH	N.A.
Water Solubility	N.A.
Flammability	Flash point below 73°F/23°C
Flash Point	65°F
Viscosity	N.A.
Lower Explosion Level	2%
Upper Explosion Level	12.7%
Vapor Pressure	N.A.
Vapor Density	2.1 (20°C) (ether = 1)
Melting Point	N.A.
Freezing Point	-5°F

Low Boiling Point	195°F
High Boiling Point	200°F
Decomposition Pt	N.A.
Auto Ignition Temp	750°F
Evaporation Rate	N.A.
VOC Composite Partial Pressure	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

None.

Incompatible Materials

Oxidizing agents, acids.

Hazardous Reactions/Polymerization

Will not occur.

Hazardous Decomposition Products

None known.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

No data available.

Serious Eye Damage/Irritation

Causes serious eye irritation.

Carcinogenicity

No data available.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Respiratory/Skin Sensitization

No data available.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration Hazard

No data available.

Acute Toxicity

0000067-63-0 ISOPROPYL ALCOHOL

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (Rat, Inhalation) = 16,000 ppm/8H Reference : Registry of Toxic Effects of Chemical Substances If ingested causes drunkenness and vomiting. Inhalation can irritate the nose and throat.

LC50 (rat): 17000 ppm (4-hour exposure); cited as 12000 ppm (8-hour exposure) (18)

LD50 (oral, male rat): 4710 mg/kg (cited as 6.0 mL/kg) (19)

LD50 (oral, mouse): 3600 mg/kg (20, unconfirmed)

LD50 (dermal, rabbit): 12870 mg/kg (cited as 16.4 mL/kg) (14)

Potential Health Effects - Miscellaneous

0000067-63-0 ISOPROPYL ALCOHOL

The following medical conditions may be aggravated by exposure: dermatitis, respiratory disease. Developmental toxicity was seen in rat's offspring at doses that were maternally toxic. Contact will cause moderate to severe redness and swelling, itching, tingling sensation, painful burning. May cause injury to the cornea of the eyes. Prolonged or repeated exposure may cause damage to any of the following organs/systems: liver. Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available.

Persistence and Degradability

No data available.

Bio-Accumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORTATION INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN number:	UN3175	UN3175	UN3175
Proper shipping name:	Solids containing flammable liquid, n.o.s. (isopropanol)	Solids containing flammable liquid, n.o.s. (isopropanol)	Solids containing flammable liquid, n.o.s. (isopropanol)
Hazard class:	4.1	4.1	4.1
Packaging group:	II	II	II
Hazardous substance (RQ):	N.A.	N.A.	N.A.
Marine Pollutant:	N.A.	N.A.	N.A.
Note / Special Provision:	(LTD QTY)	(LTD QTY)	(LTD QTY)
Toxic-Inhalation Hazard:	N.A.	N.A.	N.A.

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000067-63-0	ISOPROPYL ALCOHOL	65% - 85%	SARA313, SARA312, VOC, TSCA, ACGIH, OSHA

SECTION 16) OTHER INFORMATION


Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 1
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	B

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 1.0:

Revision Date: Feb 07, 2024

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.