

Product Data Sheet

No. 11801 - 06/23

RUBBERIZED LEAK REPAIR

CARB MIR \leq 1.60 (FLEXIBLE COATING)

PRODUCT NUMBERS: 1805 - BLACK 15 OZ. NET WEIGHT AEROSOL

I. GENERAL DESCRIPTION

Features: Aervoe Rubberized Leak Repair dries quick with a flexible rubber material designed to seal water leaks and cracks. It penetrates deep into the surface to assure a firm, tough bond.

Benefits: Excellent adhesion to concrete, wood, felt, gypsum, plastic, glass and metal. Forms a tough waterproof seal as it creeps into cracks and bonds to the surface providing rust and corrosion inhibiting qualities while filling surface pores. The protective film withstands normal hydrostatic pressure.

Applications: Use on metal edging and flashings (including galvanized), gutters (PVC, metal or galvanized), roofing (composition and metal), and other metal, wood (including cut tree limbs), concrete, masonry or gypsum surfaces.

Directions: For maximum adhesion, surface must be clean, dry and free of grease, rust, scale or any other loose particles. Shake can for at least one minute after agitator ball begins to rattle and during use. Hold 8-10" from the surface to be sprayed and press spray head firmly. Apply with steady, even strokes. Clear spray tip

after each use by turning can upside down and spraying for 2-3 seconds.

- Gutters - apply to inside area 2-3 inches beyond the leak. Additional material can be applied to the outside area for increased strength and durability.
- Drip Edges & Eaves - apply to any gaps to seal from windblown water intrusion.
- Composition Roofing - apply to wood or felt underlayment of loose shingles before tacking in place.
- Vent stacks and skylights - apply around edges and joints to stop water intrusion.
- Tree limbs - seal fresh cuts to prevent insect attack.
- Concrete/Masonry/Gypsum - start in the center area of the crack to fill in and seal. Successive layers should be wider and thin around the edges to limit peeling. Final width of the patch should be about 3-4 inches.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc. Not for drinking water or food systems. Not FDA approved and not an electrical insulator. Not for sealing pin holes in air or water lines under high pressure. Please check all plastic surfaces for adhesion and compatibility before each use.

Packaging:

Aerosol:	Cans (20 oz.)	15 oz. net wt. (425 g)	17.1 fl. oz. (506 mL)
	Case (12/case):	16 lbs. (7.3 kg)	0.55 CF (0.016 CM)



Aervoe Industries, Inc.
P.O. Box 485, Gardnerville, NV 89410



(775) 783-3100 Phone • (775) 782-5687 Fax • (800) 227-0196 Customer Service
www.aervoe.com • mailbox@aervoe.com

II. CHARACTERISTICS & PROPERTIES

Specifications:

Complies with CARB flexible coating MIR regulations for aerosol coatings.

Appearance:

Gloss at 60°<5

Coverage:

Theoretical—at 1 mil dry40 ft²/can

Practical—at ½ mil dry80 ft²/can

Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch45 min.

Full cure72 hrs.

To recoatBefore 2 hrs. or after 72 hrs.

Performance and Chemical Properties:

Weight per gallon6.88 lbs/gal

Specific gravity0.82

Flammability: Label markingExtremely flammable

Flash point<0°F (-18°C)

Operating temperature range50° to 90°F (10° to 32°C)

Percent solids by weight30%

Percent solids by volume18%

CARB MIR (flexible coating)<1.6

Exterior durabilityExcellent

AdhesionExcellent

Base Materials:

Resin systemSynthetic Rubber

Solvents (top two)n-Butyl Acetate, VM&P Naphtha

Propellant systemHydrocarbon

III. SHIPPING, STORAGE AND HEALTH

UN number UN1950

Proper Shipping Description Aerosols

Hazard Class 2.1

Packing Group N/A

Limited Quantity Yes

Warehouse storage level number NFPA 30B Level 2

Storage temperature 32° to 120°F (0° to 49°C)

Shelf life 1 to 2 years

HMIS ratings

Health 2

Fire 3

Reactivity 1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.